www.coresvn.cn Page 1 of 1

# **CELOSE MES 1075**

Hydroxypropyl methylcellulose

## **Product description**

Coresyn

CELOSE MES 1075 is a delayed-solubility hydroxyethyl methylcellulose (HEMC) mainly used as a water retention agent, viscosity regulator, and rheological agent in dry-mixed systems and pre-mixed systems. Its high viscosity property offers excellent water retention, preventing moisture loss during applications to effectively avoid cracking. Additionally, it extends the open time of tile adhesives while significantly enhancing their workability. Due to its exceptional stability and delayed solubility properties, CELOSE ME S1075 is also widely used in architectural coatings.

## **Application**

Dry mixed mortar

Pre-mixed mortar

Paints & coatings

#### **Benefits**

Long open time

Good water retention

#### Typical properties

Appearance	Off white powder
Solubility	Water soluble
Loss on dry, % max.	8
pH value	6-8.5
Viscosity <sup>(1)</sup> , mPa.s	35000-45000

(1)2% solution in water, Brookfield RV, Spindle 6, 20RMP, 20°C

These properties are typical but should not be considered specifications. For detailed specification rates please consult the product Certificate of Analysis

## Package and storage

CELOSE MES 1075 is packed in 25kg paper bag net. Supplied 24 Bags (600kg) on pallets each. CELOSE MES 1075 is non-perishable powder It is recommended to use the product in rotation on a first-in-first-out basis. The product should be stored in dry and clean conditions in its original packing and away from heat.